



PH690- AVIATION FUEL HOSE

Applicable Standard : E1 1529 Type-C / ISO 1825 Type-C

Construction

Inner tube Black colour, Synthetic rubber resistant to oil

Reinforcement Plies of synthetic textile cords

Cover Black colour, synthetic conductive cover resistant to oil, ozone and abrasion

Application Aircraft fuelling with jet fuel. Portability, ease of routing and ease of installation are additional virtues.

Item Code	Dash Size	DN	ID		OD		WP		BP		DRUM REEL OD		W
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	kg/m
PH690-12	-12	19	3/4	19.0	1.38	35.0	300	20	1200	80	7.1	180	0.8
PH690-16	-16	25	1	25.4	1.63	41.5	300	20	1200	80	9.1	230	1.0
PH690-20	-20	32	1.1/4	32.0	1.89	48.0	300	20	1200	80	11.0	280	1.30
PH690-24	-24	38	1.1/2	38.0	2.19	55.5	300	20	1200	80	14.2	360	1.83
PH690-32	-32	50	2	51.0	2.66	67.5	300	20	1200	80	16.9	430	2.58
PH690-40	-40	63	2.1/2	63.0	3.23	82.0	300	20	1200	80	18.1	460	3.10



Temperature Range Continuous: -30° C to +65° C