


BSPP 60° CONE O-RING FEMALE SWIVEL


BS5200 / ISO 12151-6

HF2P-MT - BSPP OR FS


11002001



11002002



11002003



ITEM CODE	HOSE ID			TERMINATION			DIMENSIONS					
	DASH	DN	INCH	DASH	INCH	THREAD	LC (mm)	LC (inch)	LD (mm)	LD (inch)	H1 (mm)	H2 (mm)
11002001-020400	-02	04	1/8"	-04	1/4"	1/4" X 19	17	0.67	-	-	-	19
11001001-030200	-03	05	3/16"	-02	1/8"	1/8" X 28	14.8	0.58	-	-	-	14
11002001-030400	-03	05	3/16"	-04	1/4"	1/4" X 19	16.8	0.66	-	-	-	19
11001001-040200	-04	06	1/4"	-02	1/8"	1/8" X 28	15.3	0.6	-	-	-	14
11002001-040400	-04	06	1/4"	-04	1/4"	1/4" X 19	17.3	0.68	-	-	-	19
11002002-040600	-04	06	1/4"	-06	3/8"	3/8" X 19	23.3	0.92	-	-	-	22
11002001-050400	-05	08	5/16"	-04	1/4"	1/4" X 19	17.3	0.68	-	-	-	19
11002002-050600	-05	08	5/16"	-06	3/8"	3/8" X 19	23.3	0.92	-	-	-	22
11002001-060400	-06	10	3/8"	-04	1/4"	1/4" X 19	17.3	0.68	-	-	-	19
11002002-060600	-06	10	3/8"	-06	3/8"	3/8" X 19	23.3	0.92	-	-	-	22
11002002-060800	-06	10	3/8"	-08	1/2"	1/2" X 14	24.3	0.96	-	-	-	27
11002001-080600	-08	12	1/2"	-06	3/8"	3/8" X 19	18.6	0.73	-	-	-	22
11002002-080800	-08	12	1/2"	-08	1/2"	1/2" X 14	25.1	0.99	-	-	-	27
11002002-081000	-08	12	1/2"	-10	5/8"	5/8" X 14	28.4	1.12	-	-	-	27
11002002-081200	-08	12	1/2"	-12	3/4"	3/4" X 14	29	1.14	-	-	-	32
11002001-101000	-10	16	5/8"	-10	5/8"	5/8" X 14	18.1	0.71	-	-	-	27
11002002-101200	-10	16	5/8"	-12	3/4"	3/4" X 14	29	1.14	-	-	-	32
11002001-121200	-12	19	3/4"	-12	3/4"	3/4" X 14	21.6	0.85	-	-	-	32
11002002-121600	-12	19	3/4"	-16	1"	1" X 11	34	1.34	-	-	-	38
11002001-161600	-16	25	1"	-16	1"	1" X 11	24.4	0.96	-	-	-	38
11002002-162000	-16	25	1"	-20	1.1/4"	1.1/4" X 11	39.4	1.55	-	-	-	50
11002003-202000	-20	32	1.1/4"	-20	1.1/4"	1.1/4" X 11	33	1.3	-	-	-	50
11002002-202400	-20	32	1.1/4"	-24	1.1/2"	1.1/2" X 11	41.9	1.65	-	-	-	55
11002003-242400	-24	38	1.1/2"	-24	1.1/2"	1.1/2" X 11	34.8	1.37	-	-	-	55
11002002-243200	-24	38	1.1/2"	-32	2"	2" X 11	47	1.85	-	-	-	70
11002003-283200	-28	45	1.3/4"	-32	2"	2" X 11	35	1.38	-	-	-	70
11002003-323200	-32	51	2"	-32	2"	2" X 11	35	1.38	-	-	-	70