


**BSP 60° CONE O-RING FEMALE SWIVEL - 45°**


**BS5200 / ISO 12151-6**

HF2P-MT - BSPP OR FS 45


**11002401**



**11002402**



**11002403**



ITEM CODE	HOSE ID			TERMINATION			DIMENSIONS					
	DASH	DN	INCH	DASH	INCH	THREAD	LC (mm)	LC (inch)	LD (mm)	LD (inch)	H1 (mm)	H2 (mm)
11002401-040400	-04	06	1/4"	-04	1/4"	1/4" X 19	40.1	1.58	17.2	0.68	-	19
11002402-040600	-04	06	1/4"	-06	3/8"	3/8" X 19	43.8	1.72	19.4	0.76	-	22
11002402-050600	-05	08	5/16"	-06	3/8"	3/8" X 19	44.7	1.76	19.7	0.78	-	22
11002402-060600	-06	10	3/8"	-06	3/8"	3/8" X 19	44.5	1.75	19.7	0.78	-	22
11002402-060800	-06	10	3/8"	-08	1/2"	1/2" X 14	44.2	1.74	19.4	0.76	-	27
11002401-080600	-08	12	1/2"	-06	3/8"	3/8" X 19	47.5	1.87	20.9	0.82	-	22
11002402-080800	-08	12	1/2"	-08	1/2"	1/2" X 14	49.6	1.95	21.6	0.85	-	27
11002402-081000	-08	12	1/2"	-10	5/8"	5/8" X 14	51.8	2.04	23.4	0.92	-	27
11002402-081200	-08	12	1/2"	-12	3/4"	3/4" X 14	50.5	1.99	21.9	0.86	-	32
11002401-101000	-10	16	5/8"	-10	5/8"	5/8" X 14	57.4	2.26	22.2	0.87	-	27
11002402-101200	-10	16	5/8"	-12	3/4"	3/4" X 14	60.7	2.39	24.2	0.95	-	32
11002401-121200	-12	19	3/4"	-12	3/4"	3/4" X 14	67.9	2.67	26.3	1.04	-	32
11002402-121600	-12	19	3/4"	-16	1"	1" X 11	67.5	2.66	26.6	1.05	-	38
11002401-161600	-16	25	1"	-16	1"	1" X 11	80.4	3.17	31.5	1.24	-	38
11002402-162000	-16	25	1"	-20	1.1/4"	1.1/4" X 11	81.7	3.22	33.6	1.32	-	50
11002403-202000	-20	32	1.1/4"	-20	1.1/4"	1.1/4" X 11	100.5	3.96	42.2	1.66	-	50
11002402-202400	-20	32	1.1/4"	-24	1.1/2"	1.1/2" X 11	95.6	3.76	38	1.5	-	55
11002403-242400	-24	38	1.1/2"	-24	1.1/2"	1.1/2" X 11	117.7	4.63	47.8	1.88	-	55
11002402-243200	-24	38	1.1/2"	-32	2"	2" X 11	110	4.33	42.3	1.67	-	70
11002403-323200	-32	51	2"	-32	2"	2" X 11	136.6	5.38	54.7	2.15	-	70