


BSPP 60° CONE O-RING FEMALE SWIVEL - 90°


BS5200 / ISO 12151-6

HF2P-MT - BSPP OR FS 90


11002901



11002902



11002903



ITEM CODE	HOSE ID			TERMINATION			DIMENSIONS					
	DASH	DN	INCH	DASH	INCH	THREAD	LC (mm)	LC (inch)	LD (mm)	LD (inch)	H1 (mm)	H2 (mm)
11001901-030200	-03	05	3/16"	-02	1/8"	1/8" X 28	27.7	1.09	28	1.1	-	14
11002901-030400	-03	05	3/16"	-04	1/4"	1/4" X 19	27.7	1.09	32	1.26	-	19
11002901-040400	-04	06	1/4"	-04	1/4"	1/4" X 19	30.4	1.2	32	1.26	-	19
11002902-040600	-04	06	1/4"	-06	3/8"	3/8" X 19	32.1	1.26	35	1.38	-	22
11002902-050600	-05	08	5/16"	-06	3/8"	3/8" X 19	33.3	1.31	36	1.42	-	22
11002902-060600	-06	10	3/8"	-06	3/8"	3/8" X 19	33	1.3	36	1.42	-	22
11002902-060800	-06	10	3/8"	-08	1/2"	1/2" X 14	33.1	1.3	35.5	1.4	-	27
11002902-080800	-08	12	1/2"	-08	1/2"	1/2" X 14	38	1.5	40.5	1.59	-	27
11002902-081000	-08	12	1/2"	-10	5/8"	5/8" X 14	38.4	1.51	43	1.69	-	27
11002902-081200	-08	12	1/2"	-12	3/4"	3/4" X 14	38.5	1.52	40.9	1.61	-	32
11002901-101000	-10	16	5/8"	-10	5/8"	5/8" X 14	49.8	1.96	46	1.81	-	27
11002902-101200	-10	16	5/8"	-12	3/4"	3/4" X 14	51.1	2.01	48.9	1.93	-	32
11002901-121200	-12	19	3/4"	-12	3/4"	3/4" X 14	57.5	2.26	53	2.09	-	32
11002902-121600	-12	19	3/4"	-16	1"	1" X 11	56.7	2.23	53.4	2.1	-	38
11002901-161600	-16	25	1"	-16	1"	1" X 11	72.3	2.85	68	2.68	-	38
11002902-162000	-16	25	1"	-20	1.1/4"	1.1/4" X 11	71.5	2.81	71	2.8	-	50
11002903-202000	-20	32	1.1/4"	-20	1.1/4"	1.1/4" X 11	87.6	3.45	89	3.5	-	50
11002902-202400	-20	32	1.1/4"	-24	1.1/2"	1.1/2" X 11	86.9	3.42	83	3.27	-	55
11002903-242400	-24	38	1.1/2"	-24	1.1/2"	1.1/2" X 11	105	4.13	102.8	4.05	-	55
11002902-243200	-24	38	1.1/2"	-32	2"	2" X 11	102.9	4.05	95	3.74	-	70
11002903-323200	-32	51	2"	-32	2"	2" X 11	127.6	5.02	123	4.84	-	70