


### BSPP 60° CONE O-RING FEMALE SWIVEL - 45°

### BS5200 / ISO 12151-6


HF1P-WS 4SP-R12 - BSPP OR FS 45

HF1P-4SH/R13/R15 -12 -16- BSPP OR FS 45


#### 35502402



#### 35502401



#### 35502403



ITEM CODE	HOSE ID			TERMINATION			DIMENSIONS					
	DASH	DN	INCH	DASH	INCH	THREAD	LC (mm)	LC (inch)	LD (mm)	LD (inch)	H1 (mm)	H2 (mm)
35502402-060600	-06	10	3/8"	-06	3/8"	3/8" X 19	44.7	1.76	19.7	0.78	-	22
35502402-060800	-06	10	3/8"	-08	1/2"	1/2" X 14	44.3	1.74	19.4	0.76	-	27
35502402-080800	-08	12	1/2"	-08	1/2"	1/2" X 14	48.9	1.93	21.6	0.85	-	27
35502402-081000	-08	12	1/2"	-10	5/8"	5/8" X 14	51	2.01	23.4	0.92	-	27
35502402-081200	-08	12	1/2"	-12	3/4"	3/4" X 14	49.7	1.96	21.9	0.86	-	32
35502401-101000	-10	16	5/8"	-10	5/8"	5/8" X 14	57	2.24	22.2	0.87	-	27
35502402-101200	-10	16	5/8"	-12	3/4"	3/4" X 14	60.3	2.37	24.2	0.95	-	32
35502401-121200	-12	19	3/4"	-12	3/4"	3/4" X 14	68.9	2.71	27.7	1.09	-	32
35502402-121600	-12	19	3/4"	-16	1"	1" X 11	67	2.64	26.6	1.05	-	38
35502401-161600	-16	25	1"	-16	1"	1" X 11	82.2	3.24	32.9	1.3	-	41
35502402-162000	-16	25	1"	-20	1.1/4"	1.1/4" X 11	82.1	3.23	33.6	1.32	-	50
35502403-202000	-20	32	1.1/4"	-20	1.1/4"	1.1/4" X 11	100.1	3.94	42.2	1.66	-	50
35502402-202400	-20	32	1.1/4"	-24	1.1/2"	1.1/2" X 11	95.1	3.74	38	1.5	-	55
35502403-242400	-24	38	1.1/2"	-24	1.1/2"	1.1/2" X 11	120.8	4.76	47.8	1.88	-	55
35502403-323200	-32	51	2"	-32	2"	2" X 11	138.1	5.44	54.7	2.15	-	70