


**BSPP 60° CONE O-RING FEMALE SWIVEL - 90°**

**BS5200 / ISO 12151-6**


HF1P-WS 4SP-R12 - BSPP OR FS 90

HF1P-4SH/R13/R15 -12 -16 - BSPP OR FS 90


**35502902**



**35502901**



**35502903**



ITEM CODE	HOSE ID			TERMINATION			DIMENSIONS					
	DASH	DN	INCH	DASH	INCH	THREAD	LC (mm)	LC (inch)	LD (mm)	LD (inch)	H1 (mm)	H2 (mm)
35502902-060600	-06	10	3/8"	-06	3/8"	33/8" X 19	33.2	1.31	36	1.42	-	22
35502902-060800	-06	10	3/8"	-08	1/2"	1/2" X 14	33.2	1.31	35.5	1.4	-	27
35502902-080800	-08	12	1/2"	-08	1/2"	1/2" X 14	37.2	1.46	40.5	1.59	-	27
35502902-081000	-08	12	1/2"	-10	5/8"	5/8" X 14	37.6	1.48	43	1.69	-	27
35502902-081200	-08	12	1/2"	-12	3/4"	3/4" X 14	37.8	1.49	40.9	1.61	-	32
35502901-101000	-10	16	5/8"	-10	5/8"	5/8" X 14	49.4	1.94	46	1.81	-	27
35502902-101200	-10	16	5/8"	-12	3/4"	3/4" X 14	50.7	2	48.9	1.93	-	32
35502901-121200	-12	19	3/4"	-12	3/4"	3/4" X 14	57	2.24	55	2.17	-	32
35502902-121600	-12	19	3/4"	-16	1"	1" X 11	56.2	2.21	53.4	2.1	-	38
35502901-161600	-16	25	1"	-16	1"	1" X 11	72.7	2.86	70	2.76	-	41
35502902-162000	-16	25	1"	-20	1.1/4"	1.1/4" X 11	71.9	2.83	71	2.8	-	50
35502903-202000	-20	32	1.1/4"	-20	1.1/4"	1.1/4" X 11	87.1	3.43	89	3.5	-	50
35502902-202400	-20	32	1.1/4"	-24	1.1/2"	1.1/2" X 11	86.4	3.4	83	3.27	-	55
35502903-242400	-24	38	1.1/2"	-24	1.1/2"	1.1/2" X 11	108.1	4.26	102.8	4.05	-	55
35502903-323200	-32	51	2"	-32	2"	2" X 11	129.1	5.08	123	4.84	-	70