


METRIC STANDPIPE - 90°

DIN 2353 / ISO 8434-1

HF2P-MT - MSP 90

11051900



| ITEM CODE | HOSE ID | | | TERMINATION | | | DIMENSIONS | | | | | |
|-----------------|---------|----|--------|-------------|-------------|--------|------------|-----------|---------|-----------|---------|---------|
| | DASH | DN | INCH | DASH | TUBE (inch) | THREAD | LC (mm) | LC (inch) | LD (mm) | LD (inch) | H1 (mm) | H2 (mm) |
| 11051900-030600 | -03 | 05 | 3/16" | -06 | 06 | - | 27.7 | 1.09 | 39 | 1.54 | - | 06 |
| 11051900-040600 | -04 | 06 | 1/4" | -06 | 06 | - | 30.4 | 1.2 | 41 | 1.61 | - | 06 |
| 11051900-040800 | -04 | 06 | 1/4" | -08 | 08 | - | 30.4 | 1.2 | 43 | 1.69 | - | 08 |
| 11051900-041000 | -04 | 06 | 1/4" | -10 | 10 | - | 30.4 | 1.2 | 45 | 1.77 | - | 10 |
| 11051900-041200 | -04 | 06 | 1/4" | -12 | 12 | - | 30.4 | 1.2 | 45 | 1.77 | - | 12 |
| 11051900-051000 | -05 | 08 | 5/16" | -10 | 10 | - | 31.4 | 1.24 | 43 | 1.69 | - | 10 |
| 11051900-051200 | -05 | 08 | 5/16" | -12 | 12 | - | 31.4 | 1.24 | 46 | 1.81 | - | 12 |
| 11051900-061000 | -06 | 10 | 3/8" | -10 | 10 | - | 31.7 | 1.25 | 43 | 1.69 | - | 10 |
| 11051900-061200 | -06 | 10 | 3/8" | -12 | 12 | - | 31.7 | 1.25 | 43 | 1.69 | - | 12 |
| 11051900-081400 | -08 | 12 | 1/2" | -14 | 14 | - | 36.5 | 1.44 | 54 | 2.13 | - | 14 |
| 11051900-081500 | -08 | 12 | 1/2" | -15 | 15 | - | 36.5 | 1.44 | 50 | 1.97 | - | 15 |
| 11051900-081600 | -08 | 12 | 1/2" | -16 | 16 | - | 36.5 | 1.44 | 55 | 2.17 | - | 16 |
| 11051900-081800 | -08 | 12 | 1/2" | -18 | 18 | - | 36.5 | 1.44 | 51 | 2.01 | - | 18 |
| 11051900-101800 | -10 | 16 | 5/8" | -18 | 18 | - | 49.8 | 1.96 | 59 | 2.32 | - | 18 |
| 11051900-102000 | -10 | 16 | 5/8" | -20 | 20 | - | 49.8 | 1.96 | 69 | 2.72 | - | 20 |
| 11051900-102200 | -10 | 16 | 5/8" | -22 | 22 | - | 49.8 | 1.96 | 61 | 2.4 | - | 22 |
| 11051900-122000 | -12 | 19 | 3/4" | -20 | 20 | - | 57.5 | 2.26 | 71 | 2.8 | - | 20 |
| 11051900-122200 | -12 | 19 | 3/4" | -22 | 22 | - | 57.5 | 2.26 | 63 | 2.48 | - | 22 |
| 11051900-162500 | -16 | 25 | 1" | -25 | 25 | - | 72.3 | 2.85 | 88 | 3.46 | - | 25 |
| 11051900-162800 | -16 | 25 | 1" | -28 | 28 | - | 72.3 | 2.85 | 78 | 3.07 | - | 28 |
| 11051900-163000 | -16 | 25 | 1" | -30 | 30 | - | 72.3 | 2.85 | 92 | 3.62 | - | 30 |
| 11051900-203500 | -20 | 32 | 1.1/4" | -35 | 35 | - | 87.6 | 3.45 | 96 | 3.78 | - | 35 |