



# KRIMPOMATIC H130 EL

CRIMPING (STANDARD VOLUME CRIMPING)

**Code: KMPH130EL**

*Krimpmatic H130 EL is ideal for crimping hydraulic hoses up to 1" 1/4 six spirals and up to 2" four spirals.*

**MAIN FEATURES**

- Ideal for crimping any type of fitting;
- New electronic device for managing the new electro-mechanical panel;
- Warning LED for possible anomalies in the system;
- Settable re-opening time after crimping;
- Settable crimping time.



◀ **ELECTRO-MECHANICAL CONTROL WITH ELECTRONIC DEVICE**

TECHNICAL DATA	
CRIMPING FORCE	190 TON (210 US TONS)
6 SPIRALS 2 PIECES	1" 1/4
4 SP 2 PIECES	2"
INDUSTRIAL HOSE 2 PIECES	3"
MAX Ø	124 mm ((4.882"))
CRIMPING/HOUR	780
DIE OPENING	Ø + 35 mm (Ø + 1.378")
90° FITTINGS	2"
STANDARD VOLTAGE	375V-420V 50HZ 3PH
MOTOR POWER	4 Kw (5.5 Hp)
DIMENSIONS LxWxH	760x675x715 mm (29.921"x26.575"x28.149")
WEIGHT WITHOUT OIL	295 Kg (650 Lbs)
OIL	65 Lt.

INCLUDED ACCESSORIES	
ELECTRO-MECHANICAL CONTROL WITH ELECTRONIC DEVICE	
VERNIER DIAL	

OPTIONAL	
DISPENSER + PATENTED QUICK CHANGE	
BASE	
ELECTRIC PEDAL	
MARKING DIES (15 CHAR.)	
SPECIAL DIES	
BACK MIRROR	
CLEANING AND MAINTENANCE KIT	
SPECIAL VOLTAGES AVAILABLE	

WITH SPECIAL DIES Ø 104 MM UPON REQUEST | THEORETICAL WITH 1/2" Δ Ø 6 MM HOSE  
 Product specifications could be modified without prior notice.