PH442 - FUEL DISPENSING HOSE - HARD WALL



Applicable Standard : EN 1360 Type 3

Construction

Inner tube	Black colour, Synthetic rubber resistant to petrol and diesel fuel
Reinforcement	Single steel wire braid
Cover	Black Colour, synthetic rubber resistant to fuel and weather. Available in Wrap and Smooth finish*, Colour option Blue and Green available on request.
Application	Petrol and diesel fuel dispensing lines of pressure 235 psi
Optional Cover Colours	 **Blue**  **Green**

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	kg/m
PH442-10	-10	16	5/8	16.0	1.00	25.3	235	16	700	48	3.1	80	0.590
PH442-12	-12	19	3/4	19.0	1.07	27.2	235	16	700	48	3.9	100	0.661
PH442-14	-14	21	7/8	21.0	1.22	31.0	235	16	700	48	5.1	130	0.720
PH442-16	-16	25	1	25.0	1.30	33.0	235	16	700	48	5.9	150	0.657

Temperature Range : Continuous: -30°C to +55°C

Electrical resistance max : 1 X 10^2 ohms

***Smooth cover available only upto size 1"**