

**PH471 - STEAM 1 W/B**

**Applicable Standard :** IS 10655 Type 2/ISO 6134 Type 1A/BS 5342 Type 1A



**Construction**

- Inner tube**                      Black colour, EPDM rubber resistant to high temperature steam
- Reinforcement**              Single steel wire Braid
- Cover**                              Red Colour, EPDM rubber resistant to abrasion, heat and weather
- Application**                    High temperature steam Lines at constant pressure of 145 psi

**Note :**

- Black Colour Cover also available

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	kg/m
PH471-06	-06	10	3/8	10.0	0.69	17.5	145	10	1450	100	5.1	130	0.399
PH471-08	-08	12	1/2	12.5	0.87	22.0	145	10	1450	100	5.9	150	0.496
PH471-12	-12	19	3/4	19.0	1.14	29.0	145	10	1450	100	9.1	230	0.727
PH471-16	-16	25	1	25.4	1.37	34.8	145	10	1450	100	11.8	300	0.800
PH471-20	-20	32	1.1/4	31.5	1.65	42.0	145	10	1450	100	14.8	375	1.281



**Temperature Range :** Continuous: Up to +185°C Steam