PH472 - STEAM 2 W/B



Applicable Standard : Exceeds IS 10655 TYPE 3/ ISO 6134 TYPE 2A/ BS 5342 TYPE 2A

Construction

Inner tube	Black colour, EPDM rubber resistant to high temperature steam
Reinforcement	Double steel wire Braids
Cover	Red Colour, EPDM rubber resistant to heat and weather. Black colour option available on request
Application	High temperature steam Lines at constant pressure of 290 psi

Cover Options
PH482 : OIL RESISTANCE OUTER COVER CONFORMS ISO 6134 TYPE 2B/BS 5342 TYPE 2B

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	kg/m
PH472-06	-06	10	3/8	10.0	0.77	19.5	260	18	2610	180	5.1	130	0.421
PH472-08	-08	12	1/2	12.5	0.91	23.0	260	18	2610	180	5.9	150	0.589
PH472-12	-12	19	3/4	19.0	1.18	30.0	260	18	2610	180	9.1	230	0.846
PH472-16	-16	25	1	25.4	1.45	36.8	260	18	2610	180	11.8	300	1.095
PH472-20	-20	32	1.1/4	31.5	1.71	43.5	260	18	2610	180	14.8	375	1.505
PH472-24	-24	38	1.1/2	38.0	1.95	49.5	260	18	2610	180	17.9	455	1.780
PH472-32	-32	51	2	51.0	2.52	64.0	260	18	2610	180	23.6	600	2.261
PH472-40	-40	63	2.1/2	63.0	3.27	83.0	260	18	2610	180	26.6	675	4.214
PH472-48	-48	76	3	76.0	3.86	98.0	260	18	2610	180	28.5	725	4.962
PH472-64	-64	102	4	101.6	4.67	118.5	260	18	2610	180	39.4	1000	5.080

Temperature Range : Continuous: Up to +230°C Steam