PH522 - SUPER SERVICE HOSE



Applicable Standard : Exceeds EN 857 - 2 SC / EN 1829-2

Construction

Inner tube	Black colour, Synthetic rubber resistant to hot water
Reinforcement	Two high tensile steel wire braid
Cover	Black colour, Synthetic rubber resistant to abrasion and weather, oil & ozone. Available in wrap and smooth finish*. Color option Grey, Blue available on request
Application	Cleaning lines for lobby, and semi professional machines. High flexibility for use with minerals, glycols, polyglycols oils, synthetic ester oils, oils in water emlusion

Optional Cover Colours



Grey **Blue**

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	kg/m
PH522-04	-04	06	1/4	6.7	0.52	13.2	9425	650	23200	1600	3.0	75	0.326
PH522-05	-05	08	5/16	8.2	0.59	14.9	7975	550	20300	1400	3.3	85	0.369
PH522-06	-06	10	3/8	9.8	0.67	17.0	7615	525	19140	1320	3.5	90	0.459
PH522-08	-08	12	1/2	13.1	0.80	20.4	6380	440	15950	1100	5.1	130	0.626

Temperature Range : Continuous: -40°C to +155°C

***Smooth cover available only upto size 1"**