PH536 - FUEL/CNG HOSE FOR AUTOMOTIVE APPLICATION



Applicable Standard : SAE J30 - R6 / IS 15722 Class -1, Type-2

Construction

Inner tube	Black colour, Synthetic rubber resistant to oil and fuel
Reinforcement	Textile reinforcement
Cover	Black colour, Synthetic rubber resistant to abrasion and weather. Available in Wrap and Smooth finish*
Application	Designed for use in motor vechicles with CNG installations

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	kg/m
PH536-03	-03	05	3/16	4.7	0.41	10.3	315	21.5	725	50	2.0	50	0.094
PH536-04	-04	06	1/4	6.4	0.50	12.7	315	21.5	725	50	2.6	65	0.130
PH536-05	-05	08	5/16	8.0	0.56	14.3	315	21.5	725	50	3.0	75	0.155
PH536-06	-06	10	3/8	9.5	0.63	15.9	315	21.5	725	50	3.0	75	0.183
PH536-08	-08	12	1/2	12.7	0.78	19.8	315	21.5	725	50	3.9	100	0.264
PH536-10	-10	16	5/8	15.9	0.94	23.8	315	21.5	725	50	4.9	125	0.302
PH536-12	-12	19	3/4	19.0	1.13	28.6	315	21.5	725	50	5.9	150	0.372
PH536-16	-16	25	1	25.4	1.37	34.9	315	21.5	725	50	7.9	200	0.545

Temperature Range : Continuous: -40°C to +100°C

***Smooth cover available only upto size 1"**