

PH613 - OIL / FUEL DELIVERY HOSE W.P. 10 BAR



Construction :

Inner tube : Black colour, Synthetic rubber resistant to oil

Reinforcement : Plies of synthetic textile cords with two cross anti static copper wires

Cover : Black colour, Synthetic rubber resistant to oil, ozone and abrasion

Application : Mandrel built heavy duty oil discharge hose for handling grades of gasoline or petroleum oils of aromatic content upto 50% in dispensing station etc, during winter/summer seasons

Item Code	Dash Size	ID		OD		WP		BP		W
		inch	mm	inch	mm	psi	bar	psi	bar	kg/m
PH613-12	-12	3/4	19.0	1.06	27.0	150	10	435	30	0.52
PH613-16	-16	1	25.0	1.38	35.0	150	10	435	30	0.65
PH613-20	-20	1.1/4	32.0	1.65	42.0	150	10	435	30	0.80
PH613-24	-24	1.1/2	38.0	1.89	48.0	150	10	435	30	0.94
PH613-32	-32	2	51.0	2.44	62.0	150	10	435	30	1.26
PH613-40	-40	2.1/2	63.0	2.95	75.0	150	10	435	30	1.90
PH613-48	-48	3	76.0	3.46	88.0	150	10	435	30	2.20
PH613-56	-56	3.1/2	89.0	4.09	104.0	150	10	435	30	2.60
PH613-64	-64	4	102.0	4.57	116.0	150	10	435	30	2.85
PH613-80	-80	5	127.0	5.59	142.0	150	10	435	30	4.20
PH613-96	-96	6	152.0	6.54	166.0	150	10	435	30	5.30



Temperature Range : Continuous: -20°C to +80°C