PH622 - HIGH PRESSURE PLASTER SPRAY HOSE

Construction

Inner tube	Black colour, Synthetic and natural rubber blend resistant to abrasion
Reinforcement	Plies of synthetic textile cords
Cover	Black colour, Synthetic rubber resistant to ozone, weather and abrasion
Application	For High Pressure Cement/ Plaster Spraying in construction industry

Item Code	Dash Size	ID		OD		WP		BP		W
		inch	mm	inch	mm	psi	bar	psi	bar	kg/m
PH622-16	-16	1	25.0	1.54	39.0	580	40	1740	120	0.93
PH622-20	-20	1.1/4	32.0	1.81	46.0	580	40	1740	120	1.15
PH622-24	-24	1.1/2	38.0	2.13	54.0	580	40	1740	120	1.60
PH622-24	-24	1.3/8	35.0	2.00	51.0	580	40	1740	120	1.400
PH622-32	-32	2	51.0	2.72	69.0	580	40	1740	120	2.50
PH622-40	-40	2.1/2	64.0	3.39	86.0	580	40	1740	120	3.00
PH622-48	-48	3	76.0	3.86	98.0	580	40	1740	120	4.20
PH622-64	-64	4	102.0	5.12	130.0	580	40	1740	120	5.60
PH622-80	-80	5	127.0	6.18	157.0	580	40	1740	120	6.00

Temperature Range : Continuous: -30°C to +70°C