

PH649 - CONCRETE DELIVERY HOSE



Construction

Inner tube Black colour, Synthetic and natural rubber blend resistant to abrasion

Reinforcement Plies of synthetic textile cords with two cross anti static copper wires

Cover Black colour, Synthetic rubber resistant to ozone, weather and abrasion

Application Designed for concrete pumping in construction industry

Item Code	Dash Size	ID		OD		WP		BP		W
		inch	mm	inch	mm	psi	bar	psi	bar	kg/m
PH649-20	-20	1.1/4	32.0	1.93	49.0	1235	85	2465	170	1.60
PH649-24	-24	1.1/2	38.0	2.20	56.0	1235	85	2465	170	1.80
PH649-32	-32	2	51.0	2.80	71.0	1235	85	2465	170	3.00
PH649-40	-40	2.1/2	64.0	3.43	87.0	1235	85	2465	170	3.77
PH649-48	-48	3	76.0	4.02	102.0	1235	85	2465	170	4.90
PH649-56	-56	3.1/2	88.0	4.53	115.0	1235	85	2465	170	5.66
PH649-64	-64	4	102.0	5.20	132.0	1235	85	2465	170	7.36
PH649-80	-80	5	127.0	6.18	157.0	1235	85	2465	170	8.92



Temperature Range : Continuous: -30°C to +70°C