

## PH1593 - PTFE HOSE WITH POLYURETHANE COVER

Applicable Standard: Meets SAE J517 - 100R14



## Construction

Inner tube Sintered tube of polytetrafluoroethylene (P.T.F.E)

**Reinforcement** Single braid of 304 series of stainless steel wire

Cover Polyurethane, Blue Color

**Application** P.T.F.E. hose has excellent temperature characteristics at both high and low temperatures,

outstanding chemical resistance, non-contaminating properties, a low coefficient of friction, and resists deterioration. Therefore, it is generally used in applications where one or more of these

properties are critical.

Item Code	Dash Size	IO ID		OD		WP		BP		BR/r		w w
		inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	g/m
PH1593-6	-6	5/16	8.00	0.560	14.3	2500	175	10000	700	4.0	100	200
PH1593-8	-8	13/32	10.4	0.660	16.7	2000	140	8000	560	5.0	130	260
PH1593-10	-10	1/2	12.8	0.760	19.2	1750	120	7000	480	6.5	165	320
PH1593-12	-12	5/8	16.00	0.870	22.1	1270	88	5080	350	7.5	190	370
PH1593-16	-16	7/8	22.2	1.160	29.5	1000	69	4000	275	9.0	230	520



Temperature Range : -40°C to +121 °C