

PH202 - MINE SPRAY HOSE MSHA



Construction

- Inner tube** Synthetic rubber - black resistant to air and water
- Reinforcement** Single steel wire braid
- Cover** Synthetic rubber - Yellow resistant to abrasion, weather & ozone.
- Application** For general underground water spray service to control dust in mining, construction and quarries.

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	kg/m
PH202-64	-64	102	4	101.6	4.67	118.5	725	50	2900	200	35.4	900	5.887
PH 202-08	-08	12	1/2	13.1	0.91	23	1015	70	4060	280	3.5	90	0.313
PH 202-12	-12	19	3/4	19.3	1.14	29	1015	70	4060	280	4.7	120	0.54
PH 202-16	-16	25	1	25.9	1.41	35.8	1015	70	4060	280	5.9	150	0.738
PH 202-20	-20	31	1.1/4	32.4	1.69	43	1015	70	4060	280	8.3	210	0.957
PH 202-24	-24	38	1.1/2	38.7	1.98	50.3	1015	70	4060	280	9.8	250	1.195
PH 202-32	-32	51	2	51.3	2.55	64.8	1015	70	4060	280	11.8	300	1.731
PH202-48	-48	76	3	76.2	3.68	93.4	800	55	3190	220	27.5	700	5.459



Temperature Range : Continuous: -40°C to +100°C