PH242 - FIRE SUPPRESSION HOSE

Construction

Inner tube	Black Colour, Synthetic rubber resistant to oil and water
Reinforcement	Single steel wire braid
Cover	Red colour, Synthetic rubber resistant to oil,weather & flame resistance
Application	This hose is intended specifically for fire suppression systems, mining & forestry

Cover Options
PH242 : MSHA 2G

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	kg/m
PH242-04	-04	6	1/4	6.6	0.52	13.1	3265	225	13050	900	3.9	100	0.283
PH242-06	-06	10	3/8	9.8	0.67	17.1	2610	180	10440	720	4.9	125	0.400
PH242-08	-08	12	1/2	12.9	0.80	20.2	2320	160	9280	640	7.1	180	0.450
PH242-10	-10	16	5/8	16.2	0.92	23.3	1885	130	7540	520	7.9	200	0.550
PH242-12	-12	19	3/4	19.2	1.07	27.3	1525	105	6090	420	9.4	240	0.700
PH242-16	-16	25	1	25.9	1.39	35.3	1305	90	5150	355	11.8	300	1.200

Temperature Range : Continuous: -40°C to +100°C

Intermittent : +120°C