

PH302 - SEWER JET - 3000 PSI



Construction

- Inner tube** Thermoplastic Elastomer
- Reinforcement** One or more Braids of Synthetic Fiber
- Cover** Polyurethane, Blue Colour

Application Standard Sewer cleaning vehicles and cleaning equipments. Heavy duty construction for optimum cut and wear resistance with bonded tube and cover. Available in long lengths with a special cover, resistant to microbiological degradation light weight compared to conventional rubber alternatives and increased lifetime

Note :

- Special colours available on request

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	g/m
PH302-02	-02	03	1/8	3.2	0.335	8.5	3000	210	7500	525	1.2	30	57
PH302-03	-03	05	3/16	4.8	0.413	10.5	3000	210	7500	525	1.4	35	83
PH302-04	-04	06	1/4	6.4	0.505	12.8	3000	210	7500	525	1.6	40	117
PH302-06	-06	10	3/8	9.5	0.640	16.3	3000	210	7500	525	3.0	75	170
PH302-08	-08	12	1/2	12.7	0.880	22.4	3000	210	7500	525	4.0	100	318
PH302-10	-10	16	5/8	16.0	1.030	26.2	3000	210	7500	525	4.3	110	430
PH306-12	-12	20	3/4	19.0	1.160	29.5	3000	210	7500	525	4.7	120	440
PH306-16	-16	25	1	25.4	1.475	37.5	3000	210	7500	525	6.3	160	675
PH306-20	-20	32	1.1/4	31.8	1.880	47.8	3000	210	7500	525	10.2	260	1130



Temperature Range : Continuous: -40°C to +60°C