

PH320 / PH321 / PH322 - LUBRICATION GREASE HOSE



Construction

Inner tube	Thermoplastic Elastomer
Reinforcement	PH320 & PH321: One or more braids of synthetic fiber PH322: One or more braids of Aramid Fiber
Cover	Polyurethane, Black Colour
Application	High pressure mini hydraulic Lines 300 to 400 bar. Suitable for hydraulic application with increased resistance to abrasion for use with petroleum, synthetic or water based fluids. Specifically designed for diverse greasing and lubrication applications of industrial, hand held or automatic(centralized) grease distribution equipment

Note : Please contact for different working pressure and dimensions

Item Code	 ID		 OD		 WP		 BP		 BR/r		 W g/m
	inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	
PH320-3.6	9/64	3.6	0.335	8.5	5800	400	14500	1000	1.4	35	57
PH320-04	5/32	4.0	0.315	8.0	4350	300	10875	750	1.6	40	54
PH320-4.2	5/32	4.2	0.346	8.8	5800	400	14500	1000	2.0	50	65
PH321-04	5/32	4.0	0.335	8.5	5800	400	14500	1000	1.8	45	64
PH321-4.2	5/32	4.2	0.402	10.2	5800	400	14500	1000	2.4	60	75
PH322-3.3	1/8	3.3	0.353	9.0	5800	400	23200	1600	1.2	30	75
PH322-04	5/32	4.0	0.354	9.0	5800	400	23200	1600	2.0	50	92



Temperature Range : Continuous: -40°C to +60°C