PH320 / PH321 / PH322 - LUBRICATION GREASE HOSE



Construction

Inner tube Thermoplastic Elastomer

Reinforcement PH320 & PH321: One or more braids of synthetic fiber
PH322: One or more braids of Aramid Fiber

Cover Polyurethane, Black Colour

Application High pressure mini hydraulic Lines 300 to 400 bar. Suitable for hydraulic application with increased resistance to abrasion for use with petroleum, synthetic or water based fluids Specifically designed for diverse greasing and lubrication applications of industrial, hand held or automatic(centralized) grease distribution equipment

Note :

- Please contact for different working pressure and dimensions

Item Code	ID		OD		WP		BP		BR/r		W
	inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	g/m
PH320-3.6	9/64	3.6	0.335	8.5	5800	400	14500	1000	1.4	35	57
PH320-4	5/32	4.0	0.315	8.0	4350	300	10875	750	1.6	40	54
PH320-4.2	5/32	4.2	0.346	8.8	5800	400	14500	1000	2.0	50	65
PH321-4	5/32	4.0	0.335	8.5	5800	400	14500	1000	1.8	45	64
PH321-4.2	5/32	4.2	0.402	10.2	5800	400	14500	1000	2.4	60	75
PH322-3.3	1/8	3.3	0.353	9.0	5800	400	23200	1600	1.2	30	75
PH322-4	5/32	4.0	0.354	9.0	5800	400	23200	1600	2.0	50	92

Temperature Range : Continuous: -40°C to +60°C