PH340 - PAINT & AGGRESSIVE CHEMICAL SPRAY - 2W



Construction

Inner tube	PTFE (Polytetrafluoroethylene)
Reinforcement	Double steel wire braids
Cover	Polyurethane, Black Colour, Pin pricked (Optional)
Application	High Pressure hydraulic lines 150 to 450 bar compact, high pressure, light weight and low change in length. Suitable for hydraulic application with increased resistance to abrasion for use with petroleum, synthetic or water based fluids in Hydraulic systems. Suitable for Agricultural machinery, Earthmoving, safety, rescue and material handling equipment. Can be used for industrial gases and other application. Please consult manufacturer. Compact construction compared to conventional double steel wire braid rubber hoses

Note :

- Special colours available on request

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	g/m
PH340-04	-04	06	1/4	6.4	0.520	13.2	5000	350	20000	1400	4.0	100	336
PH340-06	-06	10	3/8	9.5	0.675	17.1	5000	350	20000	1400	5.0	127	483
PH340-08	-08	12	1/2	12.7	0.830	21.1	5000	350	20000	1400	7.0	178	605
PH340-12	-12	20	3/4	19.0	1.150	29.2	2900	200	11600	800	10.0	250	922

Temperature Range : Continuous: -40°C to +100°C Temp. not to exceed +70°C for Air and Water based fluids