

PH342 - PAINT SPRAY - 1W



Construction

- Inner tube** Polyamide
- Reinforcement** Single Braid of steel wire
- Cover** Polyurethane, Blue Colour, Pin pricking (Optional)
- Application** Airless paint spray systems for 100 to 350 bar. Suitable for applications requiring chemical resistance to solvents and aggressive fluids. Due to low permeation value of polyamide, the hose is also suitable for industrial gases

Note :

- Available Twin & Multi lines with different Hose combination and Size; WP at 1:2.5 ratio also available

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	g/m
PH342-03	-03	05	3/16	4.8	0.380	9.7	5000	350	20000	1400	1.2	30	138
PH342-04	-04	06	1/4	6.4	0.460	11.7	4650	320	18600	1280	1.6	40	180
PH342-05	-05	08	5/16	8.0	0.535	13.6	4000	275	16000	1100	2.0	50	220
PH342-06	-06	10	3/8	9.5	0.600	15.2	3600	250	14400	1000	2.4	60	257
PH342-08	-08	12	1/2	12.7	0.725	18.4	2750	190	11000	760	3.0	75	337
PH342-10	-10	16	5/8	16.0	0.875	22.2	2300	160	9200	640	4.3	110	450
PH342-12	-12	20	3/4	19.0	1.010	25.7	1750	120	7000	480	6.0	150	531
PH342-16	-16	25	1	25.4	1.275	32.4	1450	100	5800	400	9.1	230	660



Temperature Range : Continuous: -40°C to +100°C Temp. not to exceed +70°C for Air and Water based fluids