

## PH350 - HIGH PRESSURE JACK HOSE



Construction:

**Inner tube :** Thermoplastic Elastomer

Reinforcement: Double braids of steel wire

Cover: Polyurethane, Red Orange Colour

**Application:** Very High-Pressure hydraulic lines 300 to 700 bar compact, high pressure, light weight, high abrasion resistance and low change in length for use with petroleum, synthetic or water-based fluid in hydraulic systems. Mainly used for rescue, safety equipment, bolt tensioning tools and jacking & re-railing equipment also, suitable for earthmoving and material handling equipment

Note: Available Twin & Multi lines with different Hose combination and size. Also special colours available on request

Item Code	Dash Size	DN	ĪŌ ID		© ob		WP		BP		BR/r		w w
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	g/m
PH350-04	-04	06	1/4	6.4	0.555	14.1	10000	700	25000	1750	4.0	100	356
PH350-06	-06	10	3/8	9.5	0.690	17.5	10000	700	21750	1500	6.0	150	513
PH350-08	-08	12	1/2	12.7	0.830	21.1	7250	500	18125	1250	8.0	200	678

Temperature Range: Continuous: -40°C to +100°C Temp. not to exceed +70°C for Air and Water based fluids