PH352 - VERY HIGH PRESSURE JACK HOSE - NON CONDUCTIVE



Construction

Inner tube	Thermoplastic Elastomer
Reinforcement	Two or more braids of aramid fiber
Cover	Polyurethane, Orange Colour
Application	Non conductive Hydraulic Lines 700 bar, Compact, high pressure, light weight, high abrasion resistance and low change in length for use with petroleum, synthetic or water based fluids in hydraulic systems. Mainly used for rescue, safety equipments, bolt tensioning tools and jacking & re-railing equipment. Mainly used in applications requiring high electrical insulation or non-conductivity

Note :

- Available Twin & Multi lines with different Hose combination and size

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	g/m
PH352-02	-02	02	1/8	3.2	0.358	9.1	10000	700	40000	2800	1.0	25	76
PH352-04	-04	06	1/4	6.4	0.590	15.0	10000	700	40000	2800	1.4	35	195
PH352-06	-06	10	3/8	9.5	0.735	18.7	10000	700	40000	2800	2.2	55	275
PH352-08	-08	12	1/2	12.7	0.920	23.4	8000	550	32000	2200	4.3	110	310
PH352-40	-	04	5/32	4.0	0.375	9.6	10000	700	40000	2800	1.1	27	80

Temperature Range : Continuous: -40°C to +100°C Temp. not to exceed +70°C for Air and Water based fluids