

PH369 - Hose Protective Sleeve



Construction

Application :Polyhose Protective Sleeves are used on earthmoving machinery, mining industry and industrial equipment for wear resistance and to avoid geting people injured by burst and high pressure/temperature liquid spray

Description: Protective Sleeves are made of a high-performance nylon yarn to prevent abrasion and injuries. The special weave gives an exceptionally smooth inner wall, in which the hydraulic hose can move freely to prevent wear. Protective Sleeves are ideal for protecting people, the environment and the machine against possible leaks.

Material: For Nylon - PH369N, For Polyester - PH369P, Special Material available on request

Color:Black

Approval: RoHS, MSHA

Working Temperature :-50°C to +125°C

| PRODUCT CODE | Į. | → ← Thickness | Flat Width | Colour | ⊶⊶ Meters per box |
|--------------|----|---------------------|------------|--------|----------------------|
| | mm | mm | (+/-1 mm) | | m |
| PH369-017 | 17 | 0.8 | 30 | Black | 50 |
| PH369-020 | 20 | 0.8 | 36 | Black | 50 |
| PH369-023 | 23 | 0.8 | 40 | Black | 50 |
| PH369-025 | 25 | 0.8 | 43 | Black | 50 |
| PH369-027 | 27 | 0.8 | 45 | Black | 50 |
| PH369-031 | 31 | 0.8 | 52 | Black | 50 |
| PH369-033 | 33 | 0.8 | 55 | Black | 50 |
| PH369-036 | 36 | 0.8 | 60 | Black | 50 |
| PH369-040 | 40 | 0.8 | 66 | Black | 50 |
| PH369-044 | 44 | 0.8 | 74 | Black | 50 |
| PH369-047 | 47 | 0.8 | 77 | Black | 50 |
| PH369-053 | 53 | 0.8 | 86 | Black | 50 |
| PH369-055 | 55 | 0.8 | 90 | Black | 50 |
| PH369-060 | 60 | 0.8 | 98 | Black | 50 |
| PH369-066 | 66 | 0.8 | 106 | Black | 50 |
| PH369-073 | 73 | 0.8 | 118 | Black | 50 |
| PH369-078 | 78 | 0.8 | 126 | Black | 50 |
| PH369-085 | 85 | 0.8 | 136 | Black | 50 |

| PRODUCT CODE | IO ID | → ← Thickness | Flat Width | Colour | ⊶⊶ Meters per box |
|--------------|-------|-------------------|------------|--------|----------------------|
| | mm | mm | (+/-1 mm) | | m |
| PH369-093 | 93 | 0.8 | 150 | Black | 50 |
| PH369-112 | 112 | 0.8 | 17 | Black | 50 |