


PH382 - PTFE GAS HOSE



Construction

Inner tube	Special quality of Sintered tube of polytetrafluoroethylene (P.T.F.E)
Reinforcement	Double braids of 304 series of stainless steel wire
Application	P.T.F.E hose has an excellent temperature characteristics both in high and low temperature, Excellent chemical resistance, non contamination properties, low coefficient of friction and resists deterioration. Therefore the hose is used generally in applications where all or one of the above properties is the main criteria Transport of cryogenic at high pressures

Item Code	Dash Size	WT	ID		OD		WP		BP		BR/r		W
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	
PH382-04	-4	1.00	1/4	6.4	0.470	11.9	5300	365	15900	1095	1.6	40	236
PH382-05	-5	1.00	5/16	8.0	0.540	13.7	4560	315	13680	945	1.8	45	301
PH382-06	-6	1.00	3/8	9.5	0.580	14.7	4350	300	13050	900	2.6	65	353
PH382-08	-8	1.00	1/2	12.7	0.730	18.5	3840	265	11520	795	3.0	75	466
PH382-10	-10	1.10	5/8	16.0	0.880	22.4	3400	235	10200	705	4.5	115	612
PH382-12	-12	1.25	3/4	19.0	1.030	26.2	2900	200	8700	600	9.4	240	779
PH382-16	-16	1.40	1	25.4	1.260	32.0	2200	150	6600	450	12.6	320	966



Temperature Range : Continuous: -54°C to +204°C