

PH474 - STEAM 2W/B

Applicable Standard : IS 10655 TYPE 3 / ISO 6134 TYPE 2A



Construction

- Inner tube** chlorobutyl rubber - black resistant to high temperature steam
- Reinforcement** Double steel wire braids
- Cover** EPDM rubber - Red resistant to heat and weather. Black colour option available on request
- Application** High temperature steam lines at constant pressure of 260 psi

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	kg/m
PH474-06	-06	10	3/8	10.0	0.77	19.5	260	18	2610	180	5.1	130	0.421
PH474-08	-08	12	1/2	12.5	0.91	23.0	260	18	2610	180	5.9	150	0.589
PH474-08	-08	12	1/2	12.5	0.98	25.0	260	18	2610	180	5.9	150	0.618
PH474-12	-12	19	3/4	19.0	1.18	30.0	260	18	2610	180	9.1	230	0.846
PH474-12	-12	19	3/4	19.0	1.30	33.0	260	18	2610	180	9.1	230	0.905
PH474-16	-16	25	1	25.4	1.45	36.8	260	18	2610	180	11.8	300	1.095
PH474-16	-16	25	1	25.4	1.50	38.0	260	18	2610	180	11.8	300	1.122
PH474-20	-20	31	1.1/4	31.5	1.71	43.5	260	18	2610	180	14.8	375	1.505
PH474-24	-24	38	1.1/4	38.0	1.95	49.5	260	18	2610	180	17.9	455	1.655
PH474-24	-24	38	1.1/2	38.0	2.13	54.0	260	18	2610	180	17.9	455	1.886
PH474-32	-32	51	2	51.0	2.48	63.0	260	18	2610	180	23.6	600	2.190
PH474-32	-32	51	2	51.0	2.52	64.0	260	18	2610	180	23.6	600	2.261
PH474-40	-40	63	2.1/2	63.0	3.27	83.0	260	18	2610	180	26.6	675	4.214
PH474-48	-48	76	3	76.0	3.86	98.0	260	18	2610	180	28.5	725	4.962



Temperature Range : Continuous: Up to +230°C steam