

**PH549 - HEATER HOSE**

Applicable Standard : SAE J20 R3



**Construction**

- Inner tube** EPDM rubber - black resistant to hot water and ethylene glycol fluids
- Reinforcement** Textile reinforcement
- Cover** EPDM rubber - black resistant to abrasion, weather & ozone.
- Application** Light weight & flexible hose intended to use in heater loops of engine systems, numerous industrial, agricultural and construction application where oil is not a factor.

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	kg/m
PH549-04	-04	06	1/4	6.4	0.53	13.4	150	10	435	30	3.0	75	0.118
PH549-05	-05	08	5/16	7.9	0.59	14.9	150	10	435	30	3.3	85	0.143
PH549-06	-06	10	3/8	9.5	0.69	17.5	150	10	435	30	3.5	90	0.187
PH549-08	-08	12	1/2	12.7	0.81	20.7	150	10	435	30	3.5	90	0.229
PH549-10	-10	16	5/8	16.0	0.94	24.0	150	10	435	30	3.9	100	0.282
PH549-12	-12	19	3/4	19.0	1.06	27.0	150	10	435	30	4.7	120	0.323
PH549-14	-14	22	7/8	22.0	1.19	30.2	150	10	435	30	5.9	150	0.367
PH549-16	-16	25	1	25.4	1.34	34.0	150	10	435	30	7.1	180	0.454



**Temperature Range** : Continuous: -40°C to +125°C