

PH674 - SHOT BLASTING HOSE W.P. 12 BAR - PH1 (PREMIUM ABRASION)



Construction :

Inner tube : Black colour, Synthetic and natural rubber blend highly resistant to abrasion.

Reinforcement : Plies of synthetic textile cords with two cross antistatic copper wires

Cover : Black colour, Synthetic rubber resistant to ozone, weather and abrasion

Application : Suitably designed extreme long service heavy duty hose for use in sand, metal grits and foundry waste with conductive rubber compound to ensure static electricity dissipation with average abrasion loss of tube 35mm³ according to ISO 4649

Item Code	Dash Size	ID		OD		WP		BP		kg/m
		inch	mm	inch	mm	psi	bar	psi	bar	
PH674-08	-08	1/2	12.7	1.06	27.0	175	12	525	36	0.61
PH674-12	-12	3/4	19.0	1.34	34.0	175	12	525	36	0.80
PH674-16	-16	1	25.0	1.57	40.0	175	12	525	36	0.97
PH674-20	-20	1.1/4	32.0	1.89	48.0	175	12	525	36	1.32
PH674-24	-24	1.1/2	38.0	2.13	54.0	175	12	525	36	1.45
PH674-32	-32	2	51.0	2.87	73.0	175	12	525	36	2.20
PH674-40	-40	2.1/2	64.0	3.35	85.0	175	12	525	36	3.26
PH674-48	-48	3	76.0	3.94	100.0	175	12	525	36	3.90
PH674-64	-64	4	102.0	4.96	126.0	175	12	525	36	4.40



Temperature Range : Continuous: -30°C to +70°C