

**PH6E0 - SLURRY/MUD SUCTION AND DISCHARGE HOSE W.P 10 BAR**



**Construction**

- Inner tube** Synthetic & natural rubber blend - black resistant to abrasion
- Reinforcement** Two Plies of high tensile steel cords with steel helix
- Cover** Synthetic rubber - black resistant to abrasion, weather, oil & ozone
- Application** Heavy duty slurry hose designed for transporting abrasive & corrosive slurries in industries like waste cleaning trucks, dredging and wastewater treatment. They offer high abrasion resistance, flexible and durability ensuring efficient material handling in harsh environments.

Item Code	Dash Size	ID		OD		WP		BP		BR/r		W
		inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	kg/m
PH6E0-32	-32	2	51.0	2.71	69.0	150	10	450	30	9.8	250	2.90
PH6E0-48	-48	3	76.0	3.74	95.0	150	10	450	30	15.7	400	4.10
PH6E0-64	-64	4	102.0	4.80	122.0	150	10	450	30	21.7	550	5.60
PH6E0-80	-80	5	127.0	5.82	148.0	150	10	450	30	25.6	650	8.40
PH6E0-96	-96	6	152.0	6.88	175.0	150	10	450	30	29.5	750	10.10



**Temperature Range : -30°C to +70°C**