PH761 - HYBRID HOSE - 1W



Construction

Inner tube Thermoplastic Elastomer

Reinforcement Single Braid of Steel Wire

Cover Synthetic Rubber, Black Colour

Application Medium Pressure Hydraulic Lines 88 to 225 bar. For use with petroleum, synthetic or water based fluids in Hydraulic systems. Suitable for Agricultural machinery, Earthmoving, material handling euipment and machineries / systems

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	g/m
PH761-04	-04	06	1/4	6.4	0.500	12.7	3260	225	13100	900	2.0	50	197
PH761-06	-06	10	3/8	9.5	0.660	16.8	2610	180	10500	720	2.5	64	281
PH761-08	-08	12	1/2	12.7	0.770	19.6	2320	160	9300	640	3.5	90	367
PH761-12	-12	20	3/4	19.0	1.050	26.7	1520	105	6100	420	5.0	125	579
PH761-16	-16	25	1	25.4	1.250	31.8	1270	88	5100	352	10.0	250	720

Temperature Range : Continuous: -40°C to +100°C Temp. not to exceed +70°C for Air and Water based fluids