

PH765 - MEDIUM PRESSURE POLY - COMP HOSE



Construction

Inner tube Polytetrafluoroethylene (PTFE) - Conductive

Reinforcement One or two braids of Fiber Glass Yarn

Application P.T.F.E hose has an excellent temperature characteristics both in high and low temperature, Excellent chemical resistance, non contamination properties, low coefficient of friction and resists deterioration. Combination of the fiberglass outer braid and PTFE liner, make the hose essentially non-flammable. Ultimate fuel compatibility and Formable

Item Code	 ID (Nom)		 OD (Max)		 WP		 BP		 BR/r		 W
	inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	g/m
PH765-04	1/4	6.40	0.428	10.87	800	54.0	3200	216	2.8	70	115
PH765-05	5/16	8.00	0.499	12.68	800	54.0	3200	216	3.0	76	130
PH765-06	3/8	9.53	0.605	15.37	800	54.0	3200	216	3.3	83	165
PH765-07	7/16	10.90	0.663	16.84	800	54.0	3200	216	3.8	96	175
PH765-08	1/2	13.00	0.769	19.53	800	54.0	3200	216	5.3	134	185



Temperature Range : Continuous: -54°C to +260°C