

POLYURETHANE DUCTING - HEAVY



Construction

Wall Polyester Polyurethane

Spiral Spring Steel Wire

Properties Extremely flexible, Light in Weight, Microbe - resistance, Good chemical resistance, Good UV and ozone resistance

Application Suction & transport of abrasive solids, liquids, fine grained particles, such as dust and powder. Used in extraction of oil mist, paper & textile fibers

Note :

- Length upto 20 meters. Also special sizes are available on request

Item Code	ID		WT	VP	BR/r	W
	inch	mm	mm	bar	mm	kg/m
PH130110AANT		130	1.10	0.20	195	1.614
PH600130AANT	24	600	1.30	0.03	840	7.153
PH500130AANT	20	500	1.30	0.04	750	5.966
PH450130AANT	18	450	1.30	0.06	675	5.372
PH400130AANT	16	400	1.30	0.08	600	4.962
PH350130AANT	14	350	1.30	0.09	525	4.345
PH300130AANT	12	300	1.30	0.09	450	4.238
PH279130AANT	11	279	1.30	0.10	400	3.944
PH250130AANT	10	250	1.30	0.10	375	3.538
PH220130AANT		220	1.30	0.11	338	3.118
PH200110AANT	7.7/8	200	1.10	0.12	300	2.606
PH180110AANT	7	180	1.10	0.12	270	2.349
PH160110AANT		160	1.10	0.15	240	2.092
PH152110AANT	6	152	1.10	0.15	230	1.839
PH150110AANT		150	1.10	0.20	225	1.808
PH140110AANT	5.1/2	140	1.10	0.20	210	1.650
PH032080AANT	1.1/4	32	0.80	0.45	48	0.317
PH127110AANT	5	127	1.10	0.20	185	1.577
PH120110AANT		120	1.10	0.25	180	1.492
PH110110AANT		110	1.10	0.25	170	1.369
PH102110AANT	4	102	1.10	0.30	150	1.272
PH090090AANT	3.1/2	90	0.90	0.30	135	0.986
PH080090AANT		80	0.90	0.30	120	0.900
PH076090AANT	3	76	0.90	0.30	113	0.876
PH070090AANT		70	0.90	0.35	105	0.808
PH065090AANT		65	0.90	0.35	98	0.752
PH063090AANT	2.1/2	63	0.90	0.35	95	0.730

Item Code	 ID		 WT	 VP	 BR/r	 W
	inch	mm	mm	bar	mm	kg/m
PH060090AANT		60	0.90	0.35	90	0.629
PH051090AANT	2	51	0.90	0.40	75	0.537
PH045090AANT		45	0.90	0.40	68	0.476
PH040090AANT		40	0.90	0.45	60	0.426
PH038090AANT	1.1/2	38	0.90	0.45	55	0.405



Temperature Range : Continuous: -40°C to +90°C