

**PH442 - FUEL DISPENSING HOSE - HARD WALL**

**Applicable Standard :** EN 1360 Type 3



**Construction :**

**Inner tube :** Black colour, Synthetic rubber resistant to petrol and diesel fuel

**Reinforcement :** Single steel wire braid

**Cover :** Black Colour, synthetic rubber resistant to fuel and weather. Available in Wrap and Smooth finish\*, Colour option Blue and Green available on request.

**Application :** Petrol and diesel fuel dispensing lines of pressure 235 psi

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	kg/m
PH442-10	-10	16	5/8	16.0	1.00	25.3	235	16	700	48	3.1	80	0.590
PH442-12	-12	19	3/4	19.0	1.07	27.2	235	16	700	48	3.9	100	0.661
PH442-14	-14	21	7/8	21.0	1.22	31.0	235	16	700	48	5.1	130	0.720
PH442-16	-16	25	1	25.0	1.30	33.0	235	16	700	48	5.9	150	0.657



**Temperature Range :** Continuous: -30°C to +55°C

**Electrical resistance max :** 1 X 10<sup>2</sup> ohms

**\*Smooth cover available only upto size 1"**